## **Fabric Specifications**

		Black Label	Red Label	Yellow Label	Blue Label Atlas, Stalon XL & Altai XP
OUTER TENT	Name:	Kerlon 1800	Kerlon 1200	Kerlon 1000	Kerlon 2500
	Fabric:	40 D High Tenacity Ripstop Nylon 66	30 D High Tenacity Ripstop Nylon 66	20 D High Tenacity Ripstop Nylon 66	70 D High Tenacity Ripstop Nylon
	Treatment:	100% silicone coated on both sides with a total of 3 layers. Treated for UV resistance during dyeing and coating.			
	Weight:	55 g/m <sup>2</sup>	49 g/m <sup>2</sup>	40 g/m <sup>2</sup>	77 g/m <sup>2</sup>
	Tear Strength:	min. 18 kg (ISO 13937-4)	min. 12 kg (ISO 13937-4)	min. 8 kg (ISO 13937-4)	min. 25 kg (ISO 13937-4)
	Hydrostatic Head:	5500 mm/54 kPa (ISO 811)	5000 mm/49 kPa (ISO 811)	5000 mm/49 kPa (ISO 811)	5500 mm/54 kPa (ISO 811)
INNER TENT	Fabric:	40 Denier Ripstop Nylon	30 Denier Ripstop Nylon	10 Denier Ripstop Nylon	The Atlas and Stalon XL inner tents are made with the Black Label inner
	Treatment:	Durable Water Repellent (DWR)			tent fabric. The Altai inner tent is  made with the Red Label inner tent
	Weight:	43 g/m <sup>2</sup>	35 g/m <sup>2</sup>	20 g/m <sup>2</sup>	fabric.
FLOOR	Fabric:	100 Denier Nylon	70 Denier Nylon	70 Denier Nylon	
	Treatment:	Triple-coated Polyurethane	Triple-coated Polyurethane	Triple-coated Polyurethane	The Atlas floor and the Stalon XL floor are made with the Black Label floor fabric. The Altai floor is made with the Red Label floor fabric.
	Weight:	110 g/m <sup>2</sup>	90 g/m <sup>2</sup>	90 g/m <sup>2</sup>	
	Hydrostatic Head:	20,000 mm/196 kPa (ISO 811)	15000 mm/147 kPa (ISO 811)	15000 mm/147 kPa (ISO 811)	
	Miscellaneous:	Highly puncture & abrasion resistant.	Highly puncture & abrasion resistant.	Highly puncture & abrasion resistant.	